



FDV SPEC SHEET

Ufo T High Bay

Art. no: 102760-02-2



Ufo T High Bay



Art. no: 102760-02-2

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	27000
Lumen LED (tc=25):	27000
Beam Angle:	120
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
MacAdam (SDCM):	3
Lens (Diffuser):	Clear
UGR (<=):	26



FDV SPEC SHEET

Ufo T High Bay

Art. no: 102760-02-2



PRODUCT		ELECTRICAL DATA	
Ingress Protection:	IP65	Dimming:	0-10V
Impact Protection:	IK08	Dimming Output Type:	PWM
Corrosion Class:	C3	Output Hz:	1000-3000(Hz)
Operating Temperature [°C]:	-30 - 50	Dimming Phasecut Type:	Leading / Trailing edge
Lifetime [h]:	L80B10: 100 000	Standby power Psb (W) <:	0,5
Color:	Black	Flicker metric (Pst LM) <:	0,1
RAL:	RAL9004	Stroboscopic effect metric (SVM) <	1
Length [mm]:	280	System Power [W]:	150/120/100
Height [mm]:	169	System Voltage [V]:	230V 50Hz
Width [mm]:	280	Protection Class:	1
Diameter [mm]:	280	Max load pr circuit - B10:	9
Weight [kg]:	2	Max load pr circuit - B16:	15
Housing Material :	Aluminium	Max load pr circuit - C10:	9
Diffuser Material:	Polycarbonate	Max load pr circuit - C16:	15
Material 2:	Mechanical installed part(Steel)	Leakage current [mA]:	5
		Inrush current Imax [A]:	80
		Inrush current time [µs]:	350
		Current Output [mA]:	620
		Voltage Forward Min [V]:	2,9
		Voltage Forward Max [V]:	3
		Emergency light [h]:	No Emergency light
		Emergency light testing:	N/A
MOUNTING / CONNECTION			
Connection:		18i3 5m + 2x0,4m free end	
Mounting:		Suspended, Ceiling, Wall	