



FDV SPEC SHEET

Mika29 Pole

Art. no: 102943-5



Mika29 Pole



Art. no: 102943-5

LIGHT TECHNICAL

Lightsource Type:	LED (replaceable)
Lumen Output:	3750
Lumen LED (tc=25):	4000
Beam Angle:	140°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	4
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	Cable 6m
Mounting:	Mast

ELECTRICAL DATA

Dimming:	None
System Power [W]:	30
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	6
Max load pr circuit - B16:	10
Max load pr circuit - C10:	11
Max load pr circuit - C16:	18
Leakage current [mA]:	0,7
Inrush current I _{max} [A]:	40
Socket / Cap-Base:	N/A
Voltage Forward Min [V]:	8
Voltage Forward Max [V]:	9,4



FDV SPEC SHEET

Mika29 Pole

Art. no: 102943-5



PRODUCT	
Ingress Protection:	IP66
Impact Protection:	IK08
Corrosion Class:	C4
Wind force (EPA) [m2] at 0°:	0,146
Operating Temperature [°C]:	-25 - 45
Lifetime [h]:	L80B10: 100 000
Color:	Antracite
RAL:	RAL7016
Length [mm]:	500
Height [mm]:	523
Width [mm]:	500
Diameter [mm]:	500
Weight [kg]:	8,4