




FDV SPEC SHEET
Montana M
Art. no: 103033-60-BV-1



Montana M

IP66 230V 50/60Hz

Art. no: 103033-60-BV-1

LIGHT TECHNICAL	
Lightsource Type:	LED (built in)
Lumen Output:	8400
Lumen LED (tc=25):	9240
Beam Angle:	143°*65°
CCT (Color Temperature):	3000K/2200K
CRI / Ra:	70
Color Code:	730/722
MacAdam (SDCM):	6
Lens (Diffuser):	PMMA

MOUNTING / CONNECTION	
Connection:	Cable 8m
Cut-out [mm]:	n/a
Mounting:	Mast



FDV SPEC SHEET

Montana M

Art. no: 103033-60-BV-1



PRODUCT		ELECTRICAL DATA	
Ingress Protection:	IP66	Dimming:	DALI2, D4i
Impact Protection:	IK08	Flickerfree:	Yes
Corrosion Class:	C4	Standby power Psb (W) <:	0,5
Wind force (EPA) [m2] at 0°:	0,14	Flicker metric (Pst LM) <:	0,016
Surge Protection:	L_N = 10KV	Stroboscopic effect metric (SVM) <	0,054
Operating Temperature [°C]:	-40 - 50	System Power [W]:	60
Lifetime [h]:	L80B10: 100 000	System Voltage [V]:	230V 50Hz
Color:	Grey	Protection Class:	2
RAL:	Pantone8403C	Max load pr circuit - B10:	8
Length [mm]:	665	Max load pr circuit - B16:	13
Height [mm]:	125	Max load pr circuit - C10:	14
Width [mm]:	250	Max load pr circuit - C16:	22
Diameter [mm]:	76	Leakage current [mA]:	0,7
Weight [kg]:	6,2	Inrush current Imax [A]:	98
Housing Material :	Aluminium	Inrush current time [µs]:	108
Diffuser Material:	PMMA	Socket / Cap-Base:	Zhaga
Material 2:	Driver	Current Output [mA]:	78.8
		Voltage Forward Min [V]:	21,7
		Voltage Forward Max [V]:	22,2
		Emergency light [h]:	No Emergency light