



FDV SPEC SHEET

T-Line Louvre

Art. no: 103121-60-3



T-Line Louvre



Art. no: 103121-60-3

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	9490
Lumen LED (tc=25):	10100
Beam Angle:	60°
CCT (Color Temperature):	4000
CRI / Ra:	90
Color Code:	940
MacAdam (SDCM):	3
Lens (Diffuser):	Lens
UGR (<=):	19

MOUNTING / CONNECTION

Connection:	Track 3-Circuit
Mounting:	Suspended, Track

ELECTRICAL DATA

Dimming:	None
Flickerfree:	Yes
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <	0,4
System Power [W]:	60-45
Preset Power [W]:	60
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	14
Max load pr circuit - B16:	22
Max load pr circuit - C10:	23
Max load pr circuit - C16:	37
Inrush current Imax [A]:	30
Inrush current time [µs]:	180
Current Output [mA]:	340



FDV SPEC SHEET

T-Line Louvre

Art. no: 103121-60-3



PRODUCT	
Ingress Protection:	IP40
Impact Protection:	IK03
Operating Temperature [°C]:	-25 - 60
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9016
Length [mm]:	1493
Height [mm]:	58
Width [mm]:	62
Weight [kg]:	1,5
Housing Material :	Steel
Diffuser Material:	PMMA