



## FDV SPEC SHEET

T-Line Louvre  
Art. no: 103130-60-3-ddd



## T-Line Louvre



Art. no: 103130-60-3-ddd

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	10450
Lumen LED (tc=25):	11200
Beam Angle:	60°
CCT (Color Temperature):	3000
CRI / Ra:	90
Color Code:	930
MacAdam (SDCM):	3
Lens (Diffuser):	Lens
UGR (<=):	19

### MOUNTING / CONNECTION

Connection:	18i5 DALI Quick connection
Mounting:	Suspended

### ELECTRICAL DATA

Dimming:	DALI
Dimming Phasecut Type:	Leading edge
Flickerfree:	Yes
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	0,006
Stroboscopic effect metric (SVM) <	0,003
System Power [W]:	70-40
Preset Power [W]:	70
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	13
Max load pr circuit - B16:	21
Max load pr circuit - C10:	22
Max load pr circuit - C16:	35
Leakage current [mA]:	0,52
Inrush current Imax [A]:	17,81
Inrush current time [µs]:	288
Current Output [mA]:	400



## FDV SPEC SHEET

T-Line Louvre  
Art. no: 103130-60-3-ddd



PRODUCT	
Ingress Protection:	IP40
Impact Protection:	IK03
Operating Temperature [°C]:	-25 - 60
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9016
Length [mm]:	1495
Height [mm]:	44
Width [mm]:	62
Weight [kg]:	2,3
Housing Material :	Aluminium
Diffuser Material:	PMMA