



PRODUCT SHEET

NDL190-A

Art. no: 103271-60-2



NDL190-A



SPECIFICATIONS

| | |
|---------------------------------|---------------------|
| Lightsource Type: | LED (built in) |
| System Power [W]: | 25W |
| CCT (Color Temperature): | 3000-4000K |
| Preset CCT (Color Temperature): | 3000K |
| CRI / Ra: | 90 |
| Lumen Output: | 3190lm |
| Lumen LED (tc=25): | 3800lm |
| Beam Angle: | 60° |
| Lens (Diffuser): | Frosted |
| Dimming: | Depending on Driver |
| Flickerfree: | Yes |
| System Voltage [V]: | 230V 50Hz |
| Connection: | EPN0024 |
| Mounting: | Recessed |
| Cut-out [mm]: | 160-175mm |
| Lifetime [h]: | L80B10: 100 000h |
| Lumen/W: | 126lm/W |
| UGR (<=): | 19 |
| MacAdam (SDCM): | 3 |
| Color: | Black |
| Length [mm]: | 190mm |
| Height [mm]: | 99mm |
| Width [mm]: | 190mm |
| Diameter [mm]: | 190mm |
| Weight [kg]: | 0,52kg |
| Emergency light [h]: | No Emergency light |
| Emergency light testing: | N/A |



PRODUCT SHEET

NDL190-A

Art. no: 103271-60-2



To be recessed in insulation:

not recessed in insulation