





## FDV SPEC SHEET

Panel BL

Art. no: 103330-90-2



## Panel BL



Art. no: 103330-90-2

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	4480
Lumen LED (tc=25):	4680
Beam Angle:	90°
CRI / Ra:	90
Color Code:	930
MacAdam (SDCM):	3
Lens (Diffuser):	Micropris.
UGR (<=):	19

### MOUNTING / CONNECTION

Connection:	EPN0024
Cut-out [mm]:	1170x270
Mounting:	Recessed, Ceiling

### ELECTRICAL DATA

Dimming:	Depending on Driver
Flickerfree:	Yes
System Power [W]:	28
System Voltage [V]:	230V 50Hz
Protection Class:	2
Socket / Cap-Base:	N/A
Current Output [mA]:	700
Voltage Forward Min [V]:	30
Voltage Forward Max [V]:	40
Emergency light [h]:	No Emergency light
Emergency light testing:	N/A



## FDV SPEC SHEET

Panel BL

Art. no: 103330-90-2



PRODUCT	
Ingress Protection:	IP54
Impact Protection:	IK02
Operating Temperature [°C]:	-10 - 40
Lifetime [h]:	L80B10: 100 000
Color:	Black
Length [mm]:	1195
Height [mm]:	25
Width [mm]:	295
Weight [kg]:	1,8