




FDV SPEC SHEET

Ceto Fixed

Art. no: 28930-2-36-3



92mm



Ceto Fixed



Art. no: 28930-2-36-3

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	1100
Lumen LED (tc=25):	1428
Beam Angle:	36
CCT (Color Temperature):	3000
CRI / Ra:	95
Color Code:	930
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	18i3 Quick connection
Cut-out [mm]:	92mm
Mounting:	Recessed



FDV SPEC SHEET

Ceto Fixed

Art. no: 28930-2-36-3



PRODUCT		ELECTRICAL DATA	
To be recessed in insulation:	No	UGR (<=):	19
Ingress Protection:	IP44	Dimming:	Phase-Cut
Impact Protection:	IK02	Dimming Output Type:	Amplitude Modulation
Operating Temperature [°C]:	-20 - 45	Dimming Phasecut Type:	Leading / Trailing edge
Lifetime [h]:	L80: 100 000	Flickerfree:	Yes
Color:	White	Standby power Psb (W) <:	1
RAL:	RAL9010	Flicker metric (Pst LM) <:	1
Height [mm]:	90	Stroboscopic effect metric (SVM) <	0,4
Diameter [mm]:	98	System Power [W]:	15
Weight [kg]:	0,625	System Voltage [V]:	230V 50Hz
Housing Material :	Aluminium	Protection Class:	2
Diffuser Material:	Aluminium	Max load pr circuit - B10:	35
		Max load pr circuit - B16:	56
		Max load pr circuit - C10:	74
		Max load pr circuit - C16:	118
		Leakage current [mA]:	5
		Inrush current Imax [A]:	5
		Inrush current time [µs]:	300
		Socket / Cap-Base:	N/A
		Current Output [mA]:	350
		Voltage Forward Min [V]:	32
		Voltage Forward Max [V]:	36
		Emergency light [h]:	No Emergency light