



PRODUCT SHEET

Sargas Rotatable

Art. no: 29927-36-3



NORLUX®

Lighting Solutions

Sargas Rotatable




93mm



A+

SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	8W
CCT (Color Temperature):	2700K
CRI / Ra:	90
Lumen Output:	600lm
Lumen LED (tc=25):	724lm
Beam Angle:	36
Lens (Diffuser):	Clear
Dimming:	Phase-Cut
Flickerfree:	Yes
System Voltage [V]:	230V 50Hz
Connection:	QuickConnect
Mounting:	Recessed
Cut-out [mm]:	93mmmm
Lifetime [h]:	L80: 100 000h
Lumen/W:	75lm/W
UGR (<=):	23
MacAdam (SDCM):	3
Color:	White
Height [mm]:	56mm
Width [mm]:	100mm
Diameter [mm]:	102mm
Weight [kg]:	0,361111111111111kg
Emergency light [h]:	No Emergency light
To be recessed in insulation:	No



Sargas is an indoor downlight that can be tilted 53° and rotated 350° so you can point the light where you need it. This makes the downlight suitable for pitched roof, but also for flat ceilings to light up a wall, paintings or details you want to highlight. Comes with phase-cut driver with QuickConnect for easy installation. Cut-out Ø93mm.