





## **Tania Mini 3-Circuit**







30°	0°	30°		
C0 / C180		C90/C270		
	cd / 1000 lm			
Tania Mini DALI2 is a small spotlight in a contemporary design.				
Perfect for use at home and in other commercial settings. Front				
ring is sold separately. This version is with LED COB and no				
$changeable\ lightbulb.$				

SPECIFICATIONS         LED (built in)           Lightsource Type:         LED (built in)           System Power [W]:         14,5W           CCT (Color Temperature):         3000K           CRI / Ra:         90           Lumen Output:         1400lm           Lumen LED (tc=25):         1550lm           Beam Angle:         36           Lens (Diffuser):         Clear           Dimming:         DALI2           Flickerfree:         Yes           System Voltage [V]:         230V 50Hz           Connection:         Track 3-Circuit+dim           Mounting:         Track, Ceiling           Lifetime [h]:         L80B10: 100 000h           UGR (<=):	<b>( €</b> ☐ IP20 230V 50Hz	A** - A
System Power [W]:       14,5W         CCT (Color Temperature):       3000K         CRI / Ra:       90         Lumen Output:       1400lm         Lumen LED (tc=25):       1550lm         Beam Angle:       36         Lens (Diffuser):       Clear         Dimming:       DALI2         Flickerfree:       Yes         System Voltage [V]:       230V 50Hz         Connection:       Track 3-Circuit+dim         Mounting:       Track, Ceiling         Lifetime [h]:       L80B10: 100 000h         UGR (<=):       10         Lumen/W:       94lm/W         MacAdam (SDCM):       3         Color:       Black         Length [mm]:       167mm	SPECIFICATIONS	
CCT (Color Temperature):       3000K         CRI / Ra:       90         Lumen Output:       1400lm         Lumen LED (tc=25):       1550lm         Beam Angle:       36         Lens (Diffuser):       Clear         Dimming:       DALI2         Flickerfree:       Yes         System Voltage [V]:       230V 50Hz         Connection:       Track 3-Circuit+dim         Mounting:       Track, Ceiling         Lifetime [h]:       L80B10: 100 000h         UGR (<=):	Lightsource Type:	LED (built in)
CRI / Ra:       90         Lumen Output:       1400lm         Lumen LED (tc=25):       1550lm         Beam Angle:       36         Lens (Diffuser):       Clear         Dimming:       DALI2         Flickerfree:       Yes         System Voltage [V]:       230V 50Hz         Connection:       Track 3-Circuit+dim         Mounting:       Track, Ceiling         Lifetime [h]:       L80B10: 100 000h         UGR (<=):	System Power [W]:	14,5W
Lumen Output:       1400lm         Lumen LED (tc=25):       1550lm         Beam Angle:       36         Lens (Diffuser):       Clear         Dimming:       DALI2         Flickerfree:       Yes         System Voltage [V]:       230V 50Hz         Connection:       Track 3-Circuit+dim         Mounting:       Track, Ceiling         Lifetime [h]:       L80B10: 100 000h         UGR (<=):	CCT (Color Temperature):	3000K
Lumen LED (tc=25):       1550lm         Beam Angle:       36         Lens (Diffuser):       Clear         Dimming:       DALI2         Flickerfree:       Yes         System Voltage [V]:       230V 50Hz         Connection:       Track 3-Circuit+dim         Mounting:       Track, Ceiling         Lifetime [h]:       L80B10: 100 000h         UGR (<=):	CRI / Ra:	90
Beam Angle:       36         Lens (Diffuser):       Clear         Dimming:       DALI2         Flickerfree:       Yes         System Voltage [V]:       230V 50Hz         Connection:       Track 3-Circuit+dim         Mounting:       Track, Ceiling         Lifetime [h]:       L80B10: 100 000h         UGR (<=):	Lumen Output:	1400lm
Lens (Diffuser):       Clear         Dimming:       DALI2         Flickerfree:       Yes         System Voltage [V]:       230V 50Hz         Connection:       Track 3-Circuit*dim         Mounting:       Track, Ceiling         Lifetime [h]:       L80B10: 100 000h         UGR (<=):	Lumen LED (tc=25):	1550lm
Dimming:         DALI2           Flickerfree:         Yes           System Voltage [V]:         230V 50Hz           Connection:         Track 3-Circuit+dim           Mounting:         Track, Ceiling           Lifetime [h]:         L80B10: 100 000h           UGR (<=):         10           Lumen/W:         94lm/W           MacAdam (SDCM):         3           Color:         Black           Length [mm]:         167mm	Beam Angle:	36
Flickerfree:       Yes         System Voltage [V]:       230V 50Hz         Connection:       Track 3-Circuit+dim         Mounting:       Track, Ceiling         Lifetime [h]:       L80B10: 100 000h         UGR (<=):       10         Lumen/W:       94lm/W         MacAdam (SDCM):       3         Color:       Black         Length [mm]:       167mm	Lens (Diffuser):	Clear
System Voltage [V]:       230V 50Hz         Connection:       Track 3-Circuit+dim         Mounting:       Track, Ceiling         Lifetime [h]:       L80B10: 100 000h         UGR (<=):	Dimming:	DALI2
Connection:         Track 3-Circuit+dim           Mounting:         Track, Ceiling           Lifetime [h]:         L80B10: 100 000h           UGR (<=):         10           Lumen/W:         94lm/W           MacAdam (SDCM):         3           Color:         Black           Length [mm]:         167mm	Flickerfree:	Yes
Mounting:       Track, Ceiling         Lifetime [h]:       L80B10: 100 000h         UGR (<=):	System Voltage [V]:	230V 50Hz
Lifetime [h]:       L80B10: 100 000h         UGR (<=):	Connection:	Track 3-Circuit+dim
UGR (<=):	Mounting:	Track, Ceiling
Lumen/W:       94lm/W         MacAdam (SDCM):       3         Color:       Black         Length [mm]:       167mm	Lifetime [h]:	L80B10: 100 000h
MacAdam (SDCM): 3 Color: Black Length [mm]: 167mm	UGR (<=):	10
Color: Black Length [mm]: 167mm	Lumen/W:	94lm/W
Length [mm]: 167mm	MacAdam (SDCM):	3
-	Color:	Black
Diameter [mm].	Length [mm]:	167mm
Diameter [min]: 60mm	Diameter [mm]:	60mm
Weight [kg]: 0,5kg	Weight [kg]:	0,5kg

120°