




## FDV SPEC SHEET

Hali

Art. no: 6995-01-3



# Hali



Art. no: 6995-01-3

### LIGHT TECHNICAL

Lumen Output:	280
Lumen LED (tc=25):	550
Beam Angle:	120
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Opal
UGR (<=):	19

### MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Surface

### ELECTRICAL DATA

Dimming:	Phase-Cut
System Power [W]:	6
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	35
Max load pr circuit - B16:	56
Max load pr circuit - C10:	74
Max load pr circuit - C16:	118
Leakage current [mA]:	5
Inrush current I <sub>max</sub> [A]:	5
Inrush current time [μs]:	300
Socket / Cap-Base:	N/A
Current Output [mA]:	180



## FDV SPEC SHEET

Hali

Art. no: 6995-01-3



### PRODUCT

Ingress Protection:	IP44
Impact Protection:	IK02
Lifetime [h]:	L80B10: 100 000
Color:	White
Length [mm]:	600
Height [mm]:	8
Width [mm]:	65
Weight [kg]:	0,34