



## FDV SPEC SHEET

Ledline

Art. no: 805004-03-3-ddd



## Ledline



Art. no: 805004-03-3-ddd

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	5950
Lumen LED (tc=25):	7100
Beam Angle:	110
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Opal

### MOUNTING / CONNECTION

Connection:	LEDLine 5-pin
Mounting:	Recessed, Pendant, Ceiling, Surfac

### ELECTRICAL DATA

Dimming:	DALI
Dimming Output Type:	Amplitude Modulation
Flickerfree:	Yes
Flicker metric (Pst LM) <:	0,002
Stroboscopic effect metric (SVM) <	0,005
System Power [W]:	70
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	20
Max load pr circuit - B16:	32
Max load pr circuit - C10:	20
Max load pr circuit - C16:	32
Leakage current [mA]:	0,7
Inrush current Imax [A]:	8,54
Inrush current time [µs]:	214
Socket / Cap-Base:	N/A
Current Output [mA]:	840
Voltage Forward Min [V]:	32
Voltage Forward Max [V]:	48



## FDV SPEC SHEET

Ledline

Art. no: 805004-03-3-ddd



PRODUCT	
Ingress Protection:	IP40
Impact Protection:	IK08
Lifetime [h]:	L80B10: 100 000
Color:	White
Length [mm]:	2400
Height [mm]:	84
Width [mm]:	56
Weight [kg]:	6,6