




## FDV SPEC SHEET

Trunk

Art. no: CFL-2-1550-30WD-08-3-DA



Unit: mm



# Trunk



A<sup>++</sup>

Art. no: CFL-2-1550-30WD-0

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	7625
Lumen LED (tc=25):	7800
Beam Angle:	90°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
Lens (Diffuser):	Clear

### MOUNTING / CONNECTION

Connection:	Trunk 8-wires
Mounting:	Suspended, Ceiling

### PRODUCT

Ingress Protection:	IP20
Lifetime [h]:	L80B10: 100 000
Color:	White
Length [mm]:	1500
Height [mm]:	78,6
Width [mm]:	72,3
Weight [kg]:	1,64

### ELECTRICAL DATA

Dimming:	DALI2
Flickerfree:	Yes
System Power [W]:	50
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	11
Max load pr circuit - B16:	17
Max load pr circuit - C10:	18
Max load pr circuit - C16:	28
Inrush current I <sub>max</sub> [A]:	21,8
Inrush current time [μs]:	264