



FDV SPEC SHEET

Trunk Line

Art. no: CFTL-1550-30NR-08-3-DA



Trunk Line



Art. no: CFTL-1550-30NR-08

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	8473
Lumen LED (tc=25):	9300
Beam Angle:	60°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
Lens (Diffuser):	Lens

MOUNTING / CONNECTION

Connection:	Trunk 8-wires
Mounting:	Suspended, Ceiling

PRODUCT

Ingress Protection:	IP20
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9016
Length [mm]:	1500

ELECTRICAL DATA

Dimming:	CLO, Corridor, DALI, Push
Output Hz:	1000
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <	0,4
System Power [W]:	50
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	10
Max load pr circuit - B16:	16
Max load pr circuit - C10:	17
Max load pr circuit - C16:	27
Inrush current Imax [A]:	25
Inrush current time [µs]:	120