



FDV SPEC SHEET

Trunk Line

Art. no: CFTL-1550-30NR-08-3



Trunk Line



Art. no: CFTL-1550-30NR-08

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	8473
Lumen LED (tc=25):	9300
Beam Angle:	60
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
Lens (Diffuser):	Lens
UGR (<=):	19

MOUNTING / CONNECTION

Connection:	Trunk 8-wires
Mounting:	Suspended, Ceiling

PRODUCT

Ingress Protection:	IP20
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9016
Length [mm]:	1500

ELECTRICAL DATA

Dimming:	None
Flickerfree:	Yes
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <	0,4
System Power [W]:	50/45/40/35
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	24
Max load pr circuit - B16:	38
Max load pr circuit - C10:	28
Max load pr circuit - C16:	44
Leakage current [mA]:	0,24
Inrush current I _{max} [A]:	28
Inrush current time [μs]:	110