





## **LED Strip COB 8,2W/m Short Cut**

The LED Strip COB Short Cut offers perfect, uniform, and comfortable light without visible points or spots, creating an atmosphere that is both inviting and functional. Short distances between each cutting point, with only 13.9 mm per cutting length, provide flexible installation, allowing you to customize the lighting according to your needs and preferences. With 3-step MacAdam color consistency, you can be confident that our light remains stable and uniform over time. Choose between 2700K, 3000K, or 4000K color temperatures. This LED strip has a beam angle of 120° and a CRI of 90, accurately rendering colors in a natural way. Choose between variants with IP20 or IP65 ratings for both indoor and outdoor use.

## **VERSIONS**

| Art.No                  | Effect<br>[W] | Cold Lumen<br>[lm] | Lumen<br>Output [lm] | сст [к] | Beam Angle<br>[°] | Lens Difuser | CRI [>] | Color | Light<br>Control | Connection |
|-------------------------|---------------|--------------------|----------------------|---------|-------------------|--------------|---------|-------|------------------|------------|
| DL-101010-24-<br>2700-5 |               |                    |                      | 2700    | 120°              |              | 90      |       | nding on Dr      |            |
| DL-101011-24-<br>2700-5 |               |                    |                      | 2700    | 120°              |              | 90      |       | nding on Dr      |            |
| DL-101020-24-<br>3000-5 |               |                    |                      | 3000    | 120°              |              | 90      |       | nding on Dr      |            |
| DL-101021-24-<br>3000-5 |               |                    |                      | 3000    | 120°              |              | 90      |       | nding on Dr      |            |
| DL-101030-24-<br>4000-5 |               |                    |                      | 4000    | 120°              |              | 90      |       | nding on Dr      |            |
| DL-101031-24-<br>4000-5 |               |                    |                      | 4000    | 120°              |              | 90      |       | nding on Dr      |            |