




FDV SPEC SHEET

Rod Midi C

Art. no: 102311-30-1



Rod Midi C



Art. no: 102311-30-1

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2990
Lumen LED (tc=25):	4100
Beam Angle:	30
CCT (Color Temperature):	2700
CRI / Ra:	90
Color Code:	927
MacAdam (SDCM):	3
Lens (Diffuser):	Clear
UGR (<=):	19

MOUNTING / CONNECTION

Connection:	Track 3-Circuit
Mounting:	Track, Ceiling



FDV SPEC SHEET

Rod Midi C

Art. no: 102311-30-1



PRODUCT		ELECTRICAL DATA	
Ingress Protection:	IP20	Dimming:	None
Impact Protection:	IK02	Flickerfree:	Yes
Operating Temperature [°C]:	-20 - 45	Standby power Psb (W) <:	0,5
Lifetime [h]:	L80: 100 000	Flicker metric (Pst LM) <:	0,037
Color:	Grey	Stroboscopic effect metric (SVM) <	0,009
RAL:	RAL7035	System Power [W]:	23
Height [mm]:	115	System Voltage [V]:	230V 50Hz
Diameter [mm]:	97	Protection Class:	2
Weight [kg]:	0,66	Max load pr circuit - B10:	56
Housing Material :	Aluminium	Max load pr circuit - B16:	89
Diffuser Material:	Aluminium	Max load pr circuit - C10:	56
Material 2:	Polycarbonate	Max load pr circuit - C16:	89
		Leakage current [mA]:	0,55
		Inrush current Imax [A]:	2,025
		Inrush current time [µs]:	70
		Socket / Cap-Base:	N/A
		Current Output [mA]:	600
		Voltage Forward Min [V]:	33
		Voltage Forward Max [V]:	38
		Emergency light [h]:	No Emergency light