



PRODUCT SHEET

Cilla Micro

Art. no: 102711-24-2



Cilla Micro



60
58,5

Cut-out: Ø45



Ø55



SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	5W
CCT (Color Temperature):	3000K
CRI / Ra:	90
Lumen Output:	500lm
Lumen LED (tc=25):	929lm
Beam Angle:	24
Lens (Diffuser):	Lens
Dimming:	Depending on Driver
Flickerfree:	Yes
System Voltage [V]:	230V 50Hz
Connection:	QuickConnect
Mounting:	Recessed
Cut-out [mm]:	45mmmm
Lifetime [h]:	L80: 100 000h
Lumen/W:	100lm/W
UGR (<=):	19
MacAdam (SDCM):	3
Color:	Black
Length [mm]:	55mm
Height [mm]:	50mm
Width [mm]:	55mm
Diameter [mm]:	55mm
Weight [kg]:	0,136kg
Emergency light [h]:	No Emergency light
To be recessed in insulation:	Yes, recessed in insulation

The Cilla Micro is an elegant and functional downlight, ideal for hotels, restaurants, or modern homes. It provides comfortable and atmospheric lighting with minimal glare, thanks to its high color rendering index (CRI 95) and a warm color temperature of 2700K. With an impressive luminous efficacy of up to 100 lm/W, it creates an inviting ambience that highlights details beautifully.

With a compact design measuring 55 mm in diameter and 60 mm in height, the Cilla Micro seamlessly fits into any space. Its IP44 rating ensures it is both dust and splash resistant, making it suitable for various applications. Designed for recessed installation, it comes without a driver, which can be purchased separately. For added flexibility, you can choose from front rings in three different colors to match your interior style.

Cilla Micro the perfect combination of design, functionality, and quality.