






FDV SPEC SHEET

Panel BL

Art. no: 103320-90-2



Panel BL



Art. no: 103320-90-2

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	4430
Lumen LED (tc=25):	4650
Beam Angle:	90°
CCT (Color Temperature):	3000
CRI / Ra:	90
MacAdam (SDCM):	3
Lens (Diffuser):	Micropris.
UGR (<=):	19

MOUNTING / CONNECTION

Connection:	EPN0024
Cut-out [mm]:	570x570
Mounting:	Recessed, Ceiling

ELECTRICAL DATA

Dimming:	Depending on Driver
Flickerfree:	Yes
System Power [W]:	28
System Voltage [V]:	230V 50Hz
Protection Class:	2
Socket / Cap-Base:	N/A
Current Output [mA]:	700
Voltage Forward Min [V]:	30
Voltage Forward Max [V]:	40
Emergency light [h]:	No Emergency light
Emergency light testing:	N/A



FDV SPEC SHEET

Panel BL

Art. no: 103320-90-2



PRODUCT	
Ingress Protection:	IP54
Impact Protection:	IK02
Operating Temperature [°C]:	-10 - 40
Lifetime [h]:	L80B10: 100 000
Color:	Black
Length [mm]:	595
Height [mm]:	25
Width [mm]:	595
Weight [kg]:	1,6
Housing Material :	Aluminium
Diffuser Material:	Polystyrene