



FDV SPEC SHEET

Elle

Art. no: 103390-628-1



Elle



Art. no: 103390-628-1

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	766
Lumen LED (tc=25):	900
Beam Angle:	132,5°
CCT (Color Temperature):	27/30/4000K
Preset CCT (Color Temperature):	2700
CRI / Ra:	90
Color Code:	927
MacAdam (SDCM):	3
Lens (Diffuser):	None
UGR (<=):	29

MOUNTING / CONNECTION

Connection:	Terminal
Mounting:	Wall



FDV SPEC SHEET

Elle

Art. no: 103390-628-1



PRODUCT		ELECTRICAL DATA	
Ingress Protection:	IP44	Dimming:	Phase-Cut
Operating Temperature [°C]:	-20 - 40	Dimming Phasecut Type:	Trailing edge
Lifetime [h]:	L80: 100 000	Flickerfree:	No
Color:	Aluminium	Standby power Psb (W) <:	0,5
Length [mm]:	628	Flicker metric (Pst LM) <:	1
Height [mm]:	77	Stroboscopic effect metric (SVM) <	0,4
Width [mm]:	50	System Power [W]:	6.8
Weight [kg]:	1,375	Max. Power [W]:	8.87
Housing Material :	Aluminium 6063	System Voltage [V]:	230V 50Hz
Diffuser Material:	Polycarbonate	Protection Class:	2
		Max load pr circuit - B10:	35
		Max load pr circuit - B16:	56
		Max load pr circuit - C10:	74
		Max load pr circuit - C16:	118
		Inrush current Imax [A]:	5
		Inrush current time [µs]:	300
		Current Output [mA]:	200
		Voltage Forward Min [V]:	3
		Voltage Forward Max [V]:	3,1
		Emergency light [h]:	No Emergency light