



FDV SPEC SHEET

Elle

Art. no: 103390-628-4



Elle



Art. no: 103390-628-4

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	766
Lumen LED (tc=25):	900
Beam Angle:	132,5°
CCT (Color Temperature):	27/30/4000K
Preset CCT (Color Temperature):	2700
CRI / Ra:	90
Color Code:	927
MacAdam (SDCM):	3
Lens (Diffuser):	None
UGR (<=):	29

MOUNTING / CONNECTION

Connection:	Terminal
Mounting:	Wall



FDV SPEC SHEET

Elle

Art. no: 103390-628-4



PRODUCT	
Ingress Protection:	IP44
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80: 100 000
Color:	Brass
Length [mm]:	628
Height [mm]:	77
Width [mm]:	50
Weight [kg]:	1,375
Housing Material :	Aluminium 6063
Diffuser Material:	Polycarbonate

ELECTRICAL DATA	
Dimming:	Phase-Cut
Dimming Phasecut Type:	Trailing edge
Flickerfree:	No
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <	0,4
System Power [W]:	6.8
Max. Power [W]:	8.87
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	35
Max load pr circuit - B16:	56
Max load pr circuit - C10:	74
Max load pr circuit - C16:	118
Inrush current Imax [A]:	5
Inrush current time [µs]:	300
Current Output [mA]:	200
Voltage Forward Min [V]:	3
Voltage Forward Max [V]:	3,1
Emergency light [h]:	No Emergency light