




FDV SPEC SHEET

Tigrus 360° Square

Art. no: 26927-36-3



 80-83mm



Tigrus 360° Square



Art. no: 26927-36-3

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	550
Lumen LED (tc=25):	603
Beam Angle:	36
CCT (Color Temperature):	2700
CRI / Ra:	95
Color Code:	927
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	QuickConnect
Cut-out [mm]:	80-83mm
Mounting:	Recessed



FDV SPEC SHEET

Tigrus 360° Square

Art. no: 26927-36-3



PRODUCT		ELECTRICAL DATA	
To be recessed in insulation:	Yes, recessed in insulation	UGR (<=):	23
Ingress Protection:	IP44	Dimming:	Phase-Cut
Impact Protection:	IK02	Dimming Output Type:	PWM
Operating Temperature [°C]:	-20 - 45	Dimming Phasecut Type:	Leading / Trailing edge
Lifetime [h]:	L80: 100 000	Flickerfree:	Yes
Color:	White	Standby power Psb (W) <:	0,5
RAL:	RAL9010	Flicker metric (Pst LM) <:	1
Length [mm]:	95	Stroboscopic effect metric (SVM) <	0,4
Height [mm]:	47	System Power [W]:	7
Width [mm]:	95	System Voltage [V]:	230V 50Hz
Diameter [mm]:	95	Protection Class:	2
Weight [kg]:	0,397222222222222	Max load pr circuit - B10:	35
Housing Material :	Aluminium	Max load pr circuit - B16:	56
Diffuser Material:	Aluminium	Max load pr circuit - C10:	74
Material 2:	Polycarbonate	Max load pr circuit - C16:	118
		Leakage current [mA]:	5
		Inrush current Imax [A]:	5
		Inrush current time [µs]:	300
		Socket / Cap-Base:	N/A
		Current Output [mA]:	350
		Voltage Forward Min [V]:	12
		Voltage Forward Max [V]:	17,5
		Emergency light [h]:	No Emergency light