





FDV SPEC SHEET

Tigrus Square Double 360° Adjustable
Art. no: 27927-36-2



 175x76mm



Tigrus Square Double 360° Adjustable



Art. no: 27927-36-2

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	1100
Lumen LED (tc=25):	1200
Beam Angle:	36
CCT (Color Temperature):	2700
CRI / Ra:	95
Color Code:	927
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	QuickConnect
Cut-out [mm]:	175x76mm
Mounting:	Recessed



FDV SPEC SHEET

Tigrus Square Double 360° Adjustable

Art. no: 27927-36-2



PRODUCT		ELECTRICAL DATA	
To be recessed in insulation:	Yes, recessed in insulation	UGR (<=):	23
Ingress Protection:	IP44	Dimming:	Phase-Cut
Impact Protection:	IK02	Dimming Output Type:	Amplitude Modulation
Operating Temperature [°C]:	-20 - 45	Dimming Phasecut Type:	Leading / Trailing edge
Lifetime [h]:	L80: 100 000	Flickerfree:	Yes
Color:	Black	Standby power Psb (W) <:	0,5
RAL:	RAL9005	Flicker metric (Pst LM) <:	1
Length [mm]:	180	Stroboscopic effect metric (SVM) <	0,4
Height [mm]:	47	System Power [W]:	13
Width [mm]:	95	System Voltage [V]:	230V 50Hz
Weight [kg]:	0,65555555555556	Protection Class:	2
Housing Material :	Aluminium	Max load pr circuit - B10:	35
Diffuser Material:	Aluminium	Max load pr circuit - B16:	56
		Max load pr circuit - C10:	74
		Max load pr circuit - C16:	118
		Leakage current [mA]:	5
		Inrush current Imax [A]:	5
		Inrush current time [µs]:	300
		Socket / Cap-Base:	N/A
		Current Output [mA]:	300
		Voltage Forward Min [V]:	12
		Voltage Forward Max [V]:	17,5
		Emergency light [h]:	No Emergency light