



FDV SPEC SHEET
Phoenix
Art. no: 3450-140-1018-ddd



Phoenix



Art. no: 3450-140-1018-ddd

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	6400
Lumen LED (tc=25):	6000
Beam Angle:	140/80°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Lens
UGR (<=):	19

MOUNTING / CONNECTION

Connection:	Cable 3m
Mounting:	Pendant, Ceiling



FDV SPEC SHEET

Phoenix
Art. no: 3450-140-1018-ddd



PRODUCT	
Ingress Protection:	IP20
Impact Protection:	IK06
Operating Temperature [°C]:	-25 - 45
Lifetime [h]:	L80: 100 000
Color:	Yellow
Length [mm]:	1285
Height [mm]:	76
Width [mm]:	48
Weight [kg]:	3,75
Housing Material :	Aluminium

ELECTRICAL DATA	
Dimming:	DALI2
Dimming Output Type:	Amplitude Modulation
Flickerfree:	Yes
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	0
Stroboscopic effect metric (SVM) <	0,004
System Power [W]:	60
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	20
Max load pr circuit - B16:	32
Max load pr circuit - C10:	20
Max load pr circuit - C16:	32
Leakage current [mA]:	0,7
Inrush current Imax [A]:	8,54
Inrush current time [µs]:	214
Socket / Cap-Base:	N/A
Current Output [mA]:	1483
Voltage Forward Min [V]:	8,7
Voltage Forward Max [V]:	9,6