



## FDV SPEC SHEET

Izar

Art. no: 3932-01-2-ddd



## Izar



Art. no: 3932-01-2-ddd

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	5600
Lumen LED (tc=25):	6500
Beam Angle:	90°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Micropris.
UGR (<=):	19

### MOUNTING / CONNECTION

Connection:	QuickConnect
-------------	--------------



## FDV SPEC SHEET

Izar

Art. no: 3932-01-2-ddd



PRODUCT	
Ingress Protection:	IP20
Impact Protection:	IK06
Operating Temperature [°C]:	-25 - 45
Lifetime [h]:	L80: 100 000
Color:	White
RAL:	RAL9003
Height [mm]:	82
Width [mm]:	600
Diameter [mm]:	600
Weight [kg]:	6,1
Housing Material :	Aluminium
Diffuser Material:	Polycarbonate

ELECTRICAL DATA	
Dimming:	DALI2
Dimming Output Type:	Amplitude Modulation
Flickerfree:	Yes
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	0,016
Stroboscopic effect metric (SVM) <	0,004
System Power [W]:	48
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	23
Max load pr circuit - B16:	37
Max load pr circuit - C10:	23
Max load pr circuit - C16:	37
Leakage current [mA]:	0,7
Inrush current Imax [A]:	12
Inrush current time [µs]:	178
Socket / Cap-Base:	N/A
Current Output [mA]:	1186
Voltage Forward Min [V]:	2,6
Voltage Forward Max [V]:	2,9