




FDV SPEC SHEET

Milli Maxi

Art. no: 102740-50-3



150mm



Milli Maxi



Art. no: 102740-50-3

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2100
Lumen LED (tc=25):	2267
Beam Angle:	50
CCT (Color Temperature):	2700
CRI / Ra:	90
Color Code:	927
MacAdam (SDCM):	3
Lens (Diffuser):	Lens

MOUNTING / CONNECTION

Connection:	18i3 Quick connection
Cut-out [mm]:	150mm
Mounting:	Recessed, Ceiling

ELECTRICAL DATA

UGR (<=):	19
Dimming:	Depending on Driver
System Power [W]:	18
System Voltage [V]:	230V 50Hz
Protection Class:	3
Socket / Cap-Base:	N/A
Current Output [mA]:	500
Voltage Forward Min [V]:	33
Voltage Forward Max [V]:	38
Emergency light [h]:	No Emergency light



FDV SPEC SHEET

Milli Maxi

Art. no: 102740-50-3



PRODUCT

To be recessed in insulation:	Yes, recessed in insulation
Ingress Protection:	IP44
Impact Protection:	IK02
Operating Temperature [°C]:	-20 - 45
Lifetime [h]:	L80: 100 000
Color:	White
RAL:	RAL9010
Height [mm]:	172
Width [mm]:	164
Diameter [mm]:	160
Weight [kg]:	1,5625
Housing Material :	Aluminium
Diffuser Material:	Aluminium
Material 2:	Srpings