



PRODUCT SHEET

Driver 700mA cc 12W (9-18V) Phasecut AcTec JB&SM

Art. no: D70012NTF-02

NORLUX®

Lighting Solutions

Driver 700mA cc 12W (9-18V) Phasecut AcTec JB&SM



SPECIFICATIONS

System Power [W]:	12W
CC or CV:	CC
CC [mA]:	700 - mA
CC (forward voltage driver) [V]:	9 - 18V
Max output voltage [V]:	26
Output Current Tolerance [%]:	5%
Current Ripple [%]:	50%
Expected Lifetime:	30000h
System Voltage [V]:	230V 50HzV
Protection Class:	2
Dimming Minimum Level :	1%
Dimming Phasecut Type:	Leading / Trailing edge
Max load pr circuit - B10:	35
Max load pr circuit - B16:	56
Max load pr circuit - C10:	74
Max load pr circuit - C16:	118
Inrush current I _{max} [A]:	5A
Inrush current time [μs]:	300μs
Manufacture:	AcTEC
Manufacture P/N:	D70012NT - Driver 700mA cc 12W (9-18V) Ph
Primary Connection:	QuickConnect (L+N)
Secondary Connection:	SM Connector
Length:	109mm
Height:	22mm
Width:	40mm
Weight:	0,1kg