



PRODUCT SHEET

Driver Phasecut 650mA Max 28W 30-40V 18i3/EPN0034

Art. no: 0300-54



Driver Phasecut 650mA Max 28W 30-40V 18i3/EPN003



SPECIFICATIONS

System Power [W]:	28W
Dimming:	Phase-Cut
Output Hz:	50
Standby power P _{sb} (W) <:	1
Flicker metric (P _{st} LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
Flickerfree:	Yes
CC or CV:	CC
CC [mA]:	30 - 40mA
Max output voltage [V]:	40
Output Current Tolerance [%]:	5%
Current Ripple [%]:	5%
Expected Lifetime:	50000h
System Voltage [V]:	230V 50HzV
Protection Class:	2
Dimming Phasecut Type:	Leading / Trailing edge
Dimming output type:	PWM
Max load pr circuit - B10:	20
Max load pr circuit - B16:	32
Max load pr circuit - C10:	33
Max load pr circuit - C16:	43
Leakage current [mA]:	0,7mA
Inrush current I _{max} [A]:	12,5A
Inrush current time [μs]:	80μs
Manufacture:	Up-Shine
Primary Connection:	18i3 male
Secondary Connection:	EPN0034 female



PRODUCT SHEET

Driver Phasecut 650mA Max 28W 30-40V 18i3/EPN0034

Art. no: 0300-54



Length:	150mm
Height:	3,7mm
Width:	43mm
Weight:	0,15kg
Operating Temperature [°C]:	-20 - 40