




FDV SPEC SHEET

Silindir 70

Art. no: 101091-7-24-3-p

NORLUX®

Lighting Solutions



Silindir 70



A⁺

Art. no: 101091-7-24-3-p

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2976
Lumen LED (tc=25):	2800
Beam Angle:	24°
CCT (Color Temperature):	3000
CRI / Ra:	90
Color Code:	930
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	Track 3-Circuit
Mounting:	Track, Ceiling

ELECTRICAL DATA

Dimming:	Phase-Cut
Flicker metric (Pst LM) <:	3
Stroboscopic effect metric (SVM) <	0,4
System Power [W]:	24
System Voltage [V]:	230V 50Hz
Dimming Phasecut Type:	Leading / Trailing edge
Protection Class:	1
Max load pr circuit - B10:	27
Max load pr circuit - B16:	42
Max load pr circuit - C10:	45
Max load pr circuit - C16:	70
Leakage current [mA]:	0,1
Inrush current I _{max} [A]:	12,3
Inrush current time [µs]:	206



FDV SPEC SHEET

Silindir 70

Art. no: 101091-7-24-3-p



PRODUCT

Ingress Protection:	IP20
Lifetime [h]:	L80B10: 100 000
Color:	White
Length [mm]:	71
Height [mm]:	215
Width [mm]:	71
Weight [kg]:	1