



PRODUCT SHEET

Cylinder 60 G2

Art. no: 102262-36-3-ddd

NORLUX®

Lighting Solutions

Cylinder 60 G2



Cylinder 60 G2 is an elegant and modern spotlight, designed to deliver high light output and exceptional color rendering in various environments. With a diameter of 60mm and length of 130mm, this spotlight is both discreet and efficient. Available with beam angles of 15°, 24°, or 36° and color temperatures of 2700K, 3000K, or Dim 2 Warm (3000-1800K). CRI90 ensures excellent color rendering. Equipped with phase-cut dimming. Made of powder-coated aluminum, Cylinder 60 G2 is ideal for use in bedrooms, cafes, cabins, hotels, kitchens, and homes. The built-in driver in the sleek fixture housing provides a clean and modern appearance, while the spotlight can be tilted up to 90° and rotated 350° around its own axis for optimal adjustability. This makes Cylinder 60 perfect for both private and commercial environments.



SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	14W
CCT (Color Temperature):	4000K
CRI / Ra:	90
Lumen Output:	1400lm
Lumen LED (tc=25):	2100lm
Lens (Diffuser):	Clear
Dimming:	DALI2
Flickerfree:	Yes
System Voltage [V]:	230V 50Hz
Mounting:	Track, Ceiling
Lifetime [h]:	L80B10: 50.000h
Lumen/W:	100lm/W
Length [mm]:	130mm
Diameter [mm]:	60mm
Weight [kg]:	0,45kg
Emergency light [h]:	No Emergency light