



## PRODUCT SHEET

Tigrus Square Double 360° Adjustable


Art. no: 27927-36-2

**NORLUX®**

Lighting Solutions

# Tigrus Square Double 360° Adjustable


175x76mm



A<sup>+</sup>

### SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	13W
CCT (Color Temperature):	2700K
CRI / Ra:	95
Lumen Output:	1000lm
Lumen LED (tc=25):	1200lm
Beam Angle:	36
Lens (Diffuser):	Clear
Dimming:	Phase-Cut
Flickerfree:	Yes
System Voltage [V]:	230V 50Hz
Connection:	QuickConnect
Mounting:	Recessed
Cut-out [mm]:	175x76mm
Lifetime [h]:	L80: 100 000h
Lumen/W:	79lm/W
UGR (<=):	23
MacAdam (SDCM):	3
Color:	Black
Length [mm]:	180mm
Height [mm]:	47mm
Width [mm]:	95mm
Weight [kg]:	0,65555555555556kg
Emergency light [h]:	No Emergency light
To be recessed in insulation:	Yes, recessed in insulation



Tigrus Square Double 360° Rotatable can be mounted directly in insulation. Downlight have CRI>95 and are delivered with 2700K or Dim2Warm. The downlight can be tilted 25° and it's 360° rotatable. The luminaire connects easily without using a screwdriver. Cut-out 175x76mm.