



PRODUCT SHEET


Phoenix NWC

Art. no: 3450-NW-140-3

NORLUX®

Lighting Solutions

Phoenix NWC



SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	60W
CCT (Color Temperature):	3000-4000K
Preset CCT (Color Temperature):	3000K
CRI / Ra:	90
Lumen Output:	6400lm
Lumen LED (tc=25):	130lm
Beam Angle:	140/80°
Lens (Diffuser):	Lens
Dimming:	1-10V
Flickerfree:	Yes
System Voltage [V]:	230V 50Hz
Connection:	18i3 Quick connection
Mounting:	Pendant, Ceiling
Lifetime [h]:	L80: 100 000h
Lumen/W:	106lm/W
UGR (<=):	15
MacAdam (SDCM):	3
Color:	White
Length [mm]:	1368mm
Height [mm]:	76mm
Width [mm]:	48mm
Weight [kg]:	3,75kg
Emergency light [h]:	No Emergency light
Emergency light testing:	N/A

The Phoenix is a linear LED luminaire with up- and down light for pending down in indoor areas. The light distribution is 2000 lumen upwards with a 140° reflector and 2000 lumens downwards with a 80° reflector. It is made from durable aluminium for easy care. The color temperature is 3000 Kelvin and the reflectors secures a pleasant light. 3m wire.