



FDV SPEC SHEET

Pluto

Art. no: 3611-S-02-130-3



Pluto



Art. no: 3611-S-02-130-3

LIGHT TECHNICAL

Lumen Output:	850
Lumen LED (tc=25):	900
Beam Angle:	133°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
Lens (Diffuser):	Opal

MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Surface, Wall

ELECTRICAL DATA

Dimming:	Sensor (MW)
Dimming Output Type:	Amplitude Modulation
System Power [W]:	9
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	35
Max load pr circuit - B16:	56
Max load pr circuit - C10:	74
Max load pr circuit - C16:	118
Socket / Cap-Base:	N/A
Current Output [mA]:	81



FDV SPEC SHEET

Pluto

Art. no: 3611-S-02-130-3



PRODUCT	
Ingress Protection:	IP44
Impact Protection:	IK06
Operating Temperature [°C]:	-20 - 45
Lifetime [h]:	L80B50: 50 000
Color:	White
RAL:	RAL9016
Length [mm]:	580
Height [mm]:	66
Width [mm]:	59
Weight [kg]:	0,66