





FDV SPEC SHEET

Lobus BI

Art. no: 7016-7-30-1



Lobus BI



Art. no: 7016-7-30-1

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2356
Lumen LED (tc=25):	2600
Beam Angle:	30°
CRI / Ra:	80
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	Track 3-Circuit
Mounting:	Track, Ceiling

ELECTRICAL DATA

Dimming:	None
System Power [W]:	30
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	30
Max load pr circuit - B16:	50
Max load pr circuit - C10:	50
Max load pr circuit - C16:	85
Inrush current I _{max} [A]:	5
Inrush current time [μs]:	50
Socket / Cap-Base:	N/A
Current Output [mA]:	800
Voltage Forward Min [V]:	33,3
Voltage Forward Max [V]:	36,3



FDV SPEC SHEET

Lobus BI

Art. no: 7016-7-30-1



PRODUCT

Ingress Protection:	IP20
Operating Temperature [°C]:	0 - 35
Lifetime [h]:	L80B10: 100 000
Color:	Grey
Length [mm]:	228
Height [mm]:	180
Width [mm]:	97
Weight [kg]:	0,841
Housing Material :	Aluminium