



FDV SPEC SHEET

Galactic C
Art. no: 9067-TW-02-2-ddd



Galactic C



Art. no: 9067-TW-02-2-ddd

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen LED (tc=25):	6400
Beam Angle:	85°
CCT (Color Temperature):	2700-6500K
CRI / Ra:	80
Color Code:	827-865
MacAdam (SDCM):	3
Lens (Diffuser):	Micropris.

MOUNTING / CONNECTION

Connection:	QuickConnect
Cut-out [mm]:	Ø385-Ø415
Mounting:	Partial-recessed, Pendant, Surface

ELECTRICAL DATA

Dimming:	DALI2
Dimming Output Type:	Amplitude Modulation
System Power [W]:	60
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	13
Max load pr circuit - B16:	19
Inrush current Imax [A]:	23
Socket / Cap-Base:	N/A
Current Output [mA]:	500



FDV SPEC SHEET

Galactic C

Art. no: 9067-TW-02-2-ddd



PRODUCT	
Ingress Protection:	IP40
Operating Temperature [°C]:	-20 - 45
Lifetime [h]:	L80B10: 100 000
Color:	Black
RAL:	RAL9005
Height [mm]:	86
Diameter [mm]:	600
Weight [kg]:	6,9
Housing Material :	Aluminium