




PRODUCT FAMILY SHEET

Pavo P



Lighting Solutions



Pavo P

Surface mounted LED plafond with direct light distribution. Opal PMMA diffuser and steel housing. UGR index: =22. IP44. IK02. Options: microwave (master) sensor, Master-Slave by RF (wireless), emergency function and more.

VERSIONS

Art.No	Effect [W]	Cold Lumen [lm]	Lumen Output [lm]	CCT [K]	Beam Angle [°]	Lens Difuser	CRI [>]	Color	Light Control	Connection
8018048	32	3200		4000	120°	PMMA Opal	80	White	Sensor (MW)	Terminal
8017657	22	2090	2090	3000	118	Opal	80	White	None	Terminal
8017646	22	2090	2090	3000	118	Opal	80	White	None	Terminal
8017615	32	3500	3200	4000	120°	PMMA Opal	80	White	RF Master-S	Terminal
8017076	22	2500	2090	3000	120°	PMMA Opal	80	White	ter, Sensor (Terminal
8017007	32	3500	3200	4000	120°	PMMA Opal	80	White	ter, Sensor (Terminal
8017006	32	3500	3200	4000	120°	PMMA Opal	80	White	DALI2	Terminal
8016428	32	3650	3040	3000	120°	PMMA Opal	80	White	DALI	Terminal
8016427	32	3650	3040	3000	120°	PMMA Opal	80	White	None	Terminal
8016388	22	2500	2090	3000	120°	PMMA Opal	80	White	Master-Slav	Terminal
8016387	22	2500	2090	3000	120°	PMMA Opal	80	White	Master-Slav	Terminal
8016390	32	3650	3040	3000	120°	PMMA Opal	80	White	ter, Sensor (Terminal
8016391	40	4600	3850	3000	120°	PMMA Opal	80	White	None	Terminal
8016389	32	3650	3040	3000	120°	PMMA Opal	80	White	Master-Slav	Terminal