




PRODUCT FAMILY SHEET

Universal G2 IP44



Universal G2 IP44

Universal is an elegant and splash-proof IP44 LED luminaire designed for interior and industrial use. It features easy installation with pass-through wiring, low glare, and up to 150lm/W efficiency. The luminaire comes with a DIP switch, allowing you to customize the power level as needed, and the Kelvin can be adjusted between 3000K and 4000K. Available in lengths of 600mm, 1200mm, and 1500mm in on/off, sensor (Microwave), or DALI version. This product is also available with a microwave sensor with wireless communication between luminaires, using the Norlux Wireless Connect system for control.

VERSIONS

Art.No	Effect [W]	Cold Lumen [lm]	Lumen Output [lm]	CCT [K]	Beam Angle [°]	Lens Difuser	CRI [>]	Color	Light Control	Connection
102471-105-3	0/16/13/1	3200	2950	3000-4000K	105°	Micropris.	80	White	None	QuickConnect
102471-MW-105 -3	0/16/13/1	3200	2750	3000-4000K	105°	Micropris.	80	White	None	QuickConnect
102471-105-3- ddd	20	3200	2750	3000-4000K	105°	Micropris.	80	White	DALI2	Quickconnectx2
102472-105-3	0/35/29/	6500	6100	3000-4000K	105°	Micropris.	80	White	None	QuickConnect
102472-MW-105 -3	0/35/29/	6500	6100	3000-4000K	105°	Micropris.	80	White	Sensor (MW)	QuickConnect
102472-105-3- ddd	40	6500	6100	3000-4000K	105°	Micropris.	80	White	DALI2	QuickConnect
102473-105-3	7/40/33/	8000	7300	3000-4000K	105°	Micropris.	80	White	None	QuickConnect
102473-MW-105 -3	7/40/33/	8000	7300	3000-4000K	105°	Micropris.	80	White	None	QuickConnect
102473-105-3- ddd	47	8000	7310	3000-4000K	105°	Micropris.	80	White	DALI2	QuickConnect