


**PRODUCT DATA SHEET**

Lata Wall II 4500lm 830 60° 41W BK 3-Circuit

Art.no: 01113-00-2

*Lighting Solutions*

Lata Wall II 4500lm 830 60° 41W BK 3-Circuit



Lata Wall II by Norlux is a linear track mounted luminaire with a reflector ensuring a wide spreading of the light, illuminating large surfaces. Lata Wall II is made from molded aluminum to ensure maximum lifetime expectancy. Lata Wall II has great flexibility, tiltable 90° and rotatable 355°.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK02
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	0 - 35

**PRODUCT DATA SHEET**

Lata Wall II 4500lm 830 60° 41W BK 3-Circuit

Art.no: 01113-00-2

*Lighting Solutions*

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	109
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B50: 50 000

DRIVER	
IP (driver)	IP20
Constant current or voltage (CC or CV)	CC
Max load pr circuit - B10	31
Max load pr circuit - C16	85

DIMENSIONS	
Length (product) (mm)	226.0
Width (product) (mm)	107.0
Height (product) (mm)	248.0
Weight (product) (kg)	2.6

MATERIALS AND SURFACES	
Color	Black

INSTALLATION AND CONNECTION	
Areas of use	Shop, Showroom
Mounting	Track, Ceiling
Connection (system)	Track 3-Circuit

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++



PRODUCT DATA SHEET

Lata Wall II 4500lm 830 60° 41W BK 3-Circuit

Art.no: 01113-00-2



Lighting Solutions

LIGHT DISTRIBUTION

