

**PRODUCT DATA SHEET**

High Bay 5650lm 830 30° 46W 18i3 Grey Prismatic Screen

Art.no: 02050-2-30-6

*Lighting Solutions*

High Bay 5650lm 830 30° 46W 18i3 Grey Prismatic Screen



ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

PHOTOMETRIC DATA	
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Lightsource Type	LED (built in)

**PRODUCT DATA SHEET**

High Bay 5650lm 830 30° 46W 18i3 Grey Prismatic Screen

Art.no: 02050-2-30-6

*Lighting Solutions*

PHOTOMETRIC DATA	
Socket / Cap-Base	N/A
Lens (Diffuser)	Prismatic
Lifetime (h)	L80B10: 50.000
Manufacturer (light source)	Tridonic

DRIVER	
Manufacturer (driver)	Philips
Protection Class (driver)	1 or 2
Max Output Voltage (V)	60
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	700 - 1500
Current setting (driver)	Simpleset (Philips)
CC (forward voltage driver) (V)	24.0 - 54.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	4.0
Max load pr circuit - B10	18
Max load pr circuit - B16	30
Max load pr circuit - C10	31
Max load pr circuit - C16	51
Inrush current time (μ s)	250.0
Inrush current I _{max} (A)	18.0

DIMENSIONS	
Width (product) (mm)	430.0
Height (product) (mm)	505.0
Weight (product) (kg)	5.0

MATERIALS AND SURFACES	
Color	Aluminium

INSTALLATION AND CONNECTION	
Areas of use	Industrial
Mounting	Ceiling, Pendant



PRODUCT DATA SHEET

High Bay 5650lm 830 30° 46W 18i3 Grey Prismatic Screen

Art.no: 02050-2-30-6



Lighting Solutions

INSTALLATION AND CONNECTION

Connection (system)	18i3 Quick connection
---------------------	-----------------------

ENERGY AND CERTIFICATIONS

CE mark	Yes
Energy Efficiency Class	A++ - A

LIGHT DISTRIBUTION

