

**PRODUCT DATA SHEET**

High Bay 6000lm 840 60° 46W 18i3 Grey Prismatic Screen

Art.no: 02051-2-60-6

*Lighting Solutions*

## High Bay 6000lm 840 60° 46W 18i3 Grey Prismatic Screen



ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

PHOTOMETRIC DATA	
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	4000
Color Code	840
Lightsource Type	LED (built in)

**PRODUCT DATA SHEET**

High Bay 6000lm 840 60° 46W 18i3 Grey Prismatic Screen

Art.no: 02051-2-60-6

*Lighting Solutions*

PHOTOMETRIC DATA	
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 50.000
Manufacturer (light source)	Tridonic

DRIVER	
Manufacturer (driver)	Philips
Protection Class (driver)	1 or 2
Max Output Voltage (V)	60
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CV
CC (driver) [mA]	700 - 1500
Current setting (driver)	Simpleset (Philips)
CC (forward voltage driver) (V)	24.0 - 54.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	4.0
Max load pr circuit - B10	18
Max load pr circuit - B16	30
Max load pr circuit - C10	31
Max load pr circuit - C16	51
Inrush current time ( $\mu$ s)	250.0
Inrush current I <sub>max</sub> (A)	18.0

DIMENSIONS	
Width (product) (mm)	410.0
Height (product) (mm)	490.0
Weight (product) (kg)	5.0

MATERIALS AND SURFACES	
Color	Aluminium

INSTALLATION AND CONNECTION	
Areas of use	Industrial
Mounting	Ceiling, Pendant



**PRODUCT DATA SHEET**

High Bay 6000lm 840 60° 46W 18i3 Grey Prismatic Screen

Art.no: 02051-2-60-6



*Lighting Solutions*

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++ - A

**LIGHT DISTRIBUTION**

