

**PRODUCT DATA SHEET**

Driver DALI 900mA Panel max 45W (one4all) 18i5 DALI/EPN0034
Art.no: 0300-04



Lighting Solutions



Driver DALI 900mA Panel max 45W (one4all) 18i5 DALI/EPN0034



Tridonic DALI driver preset at 900mA, max 45W. Primary side 0,3m cable with 18i5 DALI (male). Secondary side EPN0034 (female). Can also be used as switch-dim/ push-dim.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	CLO, Corridor, DALI2, Push, Ready2Mains
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Connection 1	18i5 DALI male
Connection 2	EPN0034 female

**PRODUCT DATA SHEET**

Driver DALI 900mA Panel max 45W (one4all) 18i5 DALI/EPN0034

Art.no: 0300-04

*Lighting Solutions*

DRIVER	
Manufacturer (driver)	Tridonic
Protection Class (driver)	1 or 2
Max Output Voltage (V)	60
Dimming (driver)	CLO, Corridor, DALI2, Push, Ready2Mains
Dimming output type	Amplitude Modulation
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	900 - null
Current setting (driver)	DALI-2, I-Select 2 Plug (Tridonic), Ready2Mains
CC (forward voltage driver) (V)	25.0 - 50.0
Output Current Tolerance (%)	3.0
Current Ripple (%)	2.0
Max load pr circuit - B10	14
Max load pr circuit - B16	23
Max load pr circuit - C10	23
Max load pr circuit - C16	38
Leakage current (mA)	0.16
Inrush current time (μ s)	200.0
Inrush current I _{max} (A)	23.0

DIMENSIONS	
Length (product) (mm)	210.0
Width (product) (mm)	43.0
Height (product) (mm)	30.0
Weight (product) (kg)	0.14

ENERGY AND CERTIFICATIONS	
CE mark	Yes