

**PRODUCT DATA SHEET**

Driver On/Off 500mA max 21W 25-42V 18i3 Male/ EPN0034

Art.no: 0300-08

*Lighting Solutions*

Driver On/Off 500mA max 21W 25-42V 18i3 Male/ EPN0034



Tridonic On/Off driver preset at 500mA, max 21W. Primary side 0,3m cable with 18i3 (male). Secondary side EPN0034 (female).

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Connection 1	18i3 male
Connection 2	EPN0034 female

**PRODUCT DATA SHEET**

Driver On/Off 500mA max 21W 25-42V 18i3 Male/ EPN0034

Art.no: 0300-08

*Lighting Solutions*

DRIVER	
Manufacturer (driver)	Tridonic
Protection Class (driver)	1 or 2
Max Output Voltage (V)	60
Dimming (driver)	None
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	500 - null
Current setting (driver)	ADV Plug (Tridonic)
CC (forward voltage driver) (V)	25.0 - 42.0
Output Current Tolerance (%)	7.5
Current Ripple (%)	5.0
Max load pr circuit - B10	14
Max load pr circuit - B16	24
Max load pr circuit - C10	24
Max load pr circuit - C16	40
Leakage current (mA)	0.45
Inrush current time (μ s)	200.0
Inrush current I _{max} (A)	25.0

DIMENSIONS	
Length (product) (mm)	157.0
Width (product) (mm)	43.0
Height (product) (mm)	30.0
Weight (product) (kg)	0.2

ENERGY AND CERTIFICATIONS	
CE mark	Yes