

**PRODUCT DATA SHEET**

Driver DALI 350mA max 17W 15-49V (one4all) 18i5 DALI/EPN0034

Art.no: 0300-13

*Lighting Solutions*

Driver DALI 350mA max 17W 15-49V (one4all) 18i5 DALI/EPN0034



Tridonic DALI driver preset at 350mA, max 17W. Primary side 0,3m cable with 18i5 DALI (male). Secondary side EPN0034 (female).

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	CLO, Corridor, DALI2, Push, Ready2Mains
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Connection 1	18i5 DALI male
Connection 2	EPN0034 female

**PRODUCT DATA SHEET**

Driver DALI 350mA max 17W 15-49V (one4all) 18i5 DALI/EPN0034

Art.no: 0300-13

*Lighting Solutions*

DRIVER	
Manufacturer (driver)	Tridonic
Protection Class (driver)	1 or 2
Max Output Voltage (V)	60
Dimming (driver)	CLO, Corridor, DALI2, Push, Ready2Mains
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	350 - null
Current setting (driver)	DALI-2, I-Select 2 Plug (Tridonic), Ready2Mains
CC (forward voltage driver) (V)	15.0 - 49.0
Output Current Tolerance (%)	3.0
Current Ripple (%)	5.0
Max load pr circuit - B10	21
Max load pr circuit - B16	35
Max load pr circuit - C10	40
Max load pr circuit - C16	64
Leakage current (mA)	0.7
Inrush current time (μ s)	140.0
Inrush current I _{max} (A)	20.0

DIMENSIONS	
Length (product) (mm)	210.0
Width (product) (mm)	43.0
Height (product) (mm)	30.0
Weight (product) (kg)	0.14

ENERGY AND CERTIFICATIONS	
CE mark	Yes