

**PRODUCT DATA SHEET**

Driver DALI 500mA max 25W 20-50V (one4all) 18i5 DALI/EPN0034

Art.no: 0300-15

*Lighting Solutions*

Driver DALI 500mA max 25W 20-50V (one4all) 18i5 DALI/EPN0034



Tridonic DALI driver preset at 500mA, max 25W. Primary side 0,3m cable with 18i5 DALI (male). Secondary side EPN0034 (female).

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	CLO, Corridor, DALI2, Push, Ready2Mains
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Connection 1	18i5 DALI male
Connection 2	EPN0034 female

**PRODUCT DATA SHEET**

Driver DALI 500mA max 25W 20-50V (one4all) 18i5 DALI/EPN0034

Art.no: 0300-15

*Lighting Solutions*

DRIVER	
Manufacturer (driver)	Tridonic
Protection Class (driver)	1 or 2
Max Output Voltage (V)	60
Dimming (driver)	CLO, Corridor, DALI2, Push, Ready2Mains
Dimming output type	Amplitude Modulation
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	500 - null
Current setting (driver)	DALI-2, I-Select 2 Plug (Tridonic), Ready2Mains
CC (forward voltage driver) (V)	20.0 - 50.0
Output Current Tolerance (%)	3.0
Current Ripple (%)	2.5
Max load pr circuit - B10	19
Max load pr circuit - B16	32
Max load pr circuit - C10	31
Max load pr circuit - C16	53
Leakage current (mA)	0.15
Inrush current time (μ s)	151.0
Inrush current I _{max} (A)	26.0

DIMENSIONS	
Length (product) (mm)	210.0
Width (product) (mm)	43.0
Height (product) (mm)	30.0
Weight (product) (kg)	0.14

ENERGY AND CERTIFICATIONS	
CE mark	Yes