

**PRODUCT DATA SHEET**

Driver DALI 700mA max 35W 25-50V (one4all) 18i5 DALI/EPN0034

Art.no: 0300-17

*Lighting Solutions*

Driver DALI 700mA max 35W 25-50V (one4all) 18i5 DALI/EPN0034



Tridonic DALI driver preset at 700mA, max 35W. Primary side 0,3m cable with 18i5 DALI (male). Secondary side EPN0034 (female).

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	CLO, Corridor, DALI2, Push, Ready2Mains
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Connection 1	18i5 DALI male
Connection 2	EPN0034 female

**PRODUCT DATA SHEET**

Driver DALI 700mA max 35W 25-50V (one4all) 18i5 DALI/EPN0034

Art.no: 0300-17

*Lighting Solutions*

DRIVER	
Manufacturer (driver)	Tridonic
Protection Class (driver)	1 or 2
Max Output Voltage (V)	60
Dimming (driver)	CLO, Corridor, DALI2, Push, Ready2Mains
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	700 - null
Current setting (driver)	DALI-2, I-Select 2 Plug (Tridonic), Ready2Mains
CC (forward voltage driver) (V)	25.0 - 50.0
Output Current Tolerance (%)	3.0
Current Ripple (%)	2.0
Max load pr circuit - B10	14
Max load pr circuit - B16	23
Max load pr circuit - C10	23
Max load pr circuit - C16	38
Leakage current (mA)	0.16
Inrush current time (μ s)	200.0
Inrush current I _{max} (A)	23.0

DIMENSIONS	
Length (product) (mm)	210.0
Width (product) (mm)	43.0
Height (product) (mm)	30.0
Weight (product) (kg)	0.14

ENERGY AND CERTIFICATIONS	
CE mark	Yes