

**PRODUKTDATABLAD**

Driver DALI 700mA max 36W 30-42V 18i5 DALI/EPN0034

Art.no: 0300-2-17

*Lighting Solutions*

Driver DALI 700mA max 36W 30-42V 18i5 DALI/EPN0034



ELEKTRISKE DATA	
Beskyttelsesklasse	2
Dimmefunksjon (system)	DALI2
Spenning (V)	230V 50Hz

TEKNISK DATA	
IP (system)	IP20
Produkt Familie	Driver DALI 700mA max 36W 30-42V
Utendørs	No
Tilkobling Kabel 1	18i5 DALI hann
Tilkobling Kabel 2	EPN0034 hunn

DRIVER / BALLAST	
Produsent (driver)	Philips

**PRODUKTDATABLAD**

Driver DALI 700mA max 36W 30-42V 18i5 DALI/EPN0034

Art.no: 0300-2-17

*Lighting Solutions*

DRIVER / BALLAST	
Produsentens driverbeskrivelse	Xi 36W/m 0.7-0.85A 42V DS I TD 230V
Effekt (driver) (W)	36
Beskyttelsesklasse (driver)	2
Standbyeffekt Psb (W) <	0.5
Flimmerindikator (Pst LM) <	0.4
Stroboskopeffektindikator (SVM) <	0.1
Maks utgangsspenning (V)	60
Dimmefunksjon (driver)	DALI2
Minimum dimmenivå (%)	1.0
Type Dimming	Amplitude Modulation
IP-klasse (driver)	IP20
Forventet levetid (driver) (t)	50000
Konstant strøm eller spenning (CC eller CV)	CC
Konstant strøm (CC driver) (mA)	700 - 850
Strøminnstilling (driver)	DIP-switch
Konstant strøm (CC driftspenning driver) (V)	30.0 - 42.0
Utgangsstrøm toleranse (%)	5.0
Strømkrusning (%)	4.0
Maks belastning per kurs - B10	28
Maks belastning per kurs - B16	36
Maks belastning per kurs - C10	37
Maks belastning per kurs - C16	50
Maks belastning per kurs - C20	74
Maks belastning per kurs - C25	93
Maks belastning per kurs - C32	122
Lekkasjestrøm (mA)	0.7
Startstrøm tid (µs)	177.0
Startstrøm I _{max} (A)	16.5

MATERIALER OG OVERFLATER	
Farge	Hvit

ENERGI OG GODKJENNING	
CE-merke	Yes

**PRODUKTDATABLAD**

Driver DALI 700mA max 36W 30-42V 18i5 DALI/EPN0034

Art.no: 0300-2-17

*Lighting Solutions*