

**PRODUKTDATABLAD**

Driver Dali 700mA 30W 24-42V Dali 18i5/EPN0034

Art.no: 0300-2-49

*Lighting Solutions*

## Driver Dali 700mA 30W 24-42V Dali 18i5/EPN0034

**CE****ELEKTRISKE DATA**

Dimmefunksjon (system)	DALI
------------------------	------

**TEKNISK DATA**

Produkt Familie	Driver Dali 700mA 30W 24-42V
Tilkobling Kabel 1	18i5 DALI hann
Tilkobling Kabel 2	EPN0034 hunn

**DRIVER / BALLAST**

Produsent (driver)	Boke
Effekt (driver) (W)	30
Beskyttelsesklasse (driver)	2
Standbyeffekt Psb (W) <	0.5
Flimmerindikator (Pst LM) <	1.0
Stroboskopeffektindikator (SVM) <	0.4
Maks utgangsspenning (V)	42

**PRODUKTDATABLAD**

Driver Dali 700mA 30W 24-42V Dali 18i5/EPN0034

Art.no: 0300-2-49

*Lighting Solutions*

DRIVER / BALLAST	
Dimmefunksjon (driver)	DALI2
Minimum dimmenivå (%)	1.0
Type Dimming	Amplitude Modulation
IP-klasse (driver)	IP20
Forventet levetid (driver) (t)	100000
Konstant strøm eller spenning (CC eller CV)	CC
Konstant strøm (CC driver) (mA)	600 - 1050
Konstant strøm (CC driftspenning driver) (V)	24.0 - 42.0
Konstant spenning (CV driver) (V)	33
Utgangsstrøm toleranse (%)	5.0
Strømkrusning (%)	5.0
Maks belastning per kurs - B10	18
Maks belastning per kurs - B16	29
Maks belastning per kurs - C10	30
Maks belastning per kurs - C16	48
Maks belastning per kurs - C20	60
Maks belastning per kurs - C25	75
Lekkasjestrøm (mA)	0.7
Startstrøm tid ( $\mu$ s)	256.0
Startstrøm I <sub>max</sub> (A)	14.75

ENERGI OG GODKJENNING	
CE-merke	Yes