



PRODUCT DATA SHEET

Driver On/Off 900mA Panel max 40W 22-44V 18i3 Male/EPN0034
Art.no: 0300-24



Lighting Solutions



Driver On/Off 900mA Panel max 40W 22-44V 18i3 Male/EPN0034



On/off driver for Panel Max 45W 900mA 22-40V Primary side 18i3 male connector Secondary side EPN0034 connector

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Connection 1	18i3 male
Connection 2	EPN0034 female

**PRODUCT DATA SHEET**

Driver On/Off 900mA Panel max 40W 22-44V 18i3 Male/EPN0034

Art.no: 0300-24

*Lighting Solutions*

DRIVER	
Manufacturer (driver)	AcTEC
Protection Class (driver)	2
Flicker metric (Pst LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Dimming (driver)	None
IP (driver)	IP20
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	900 - null
Current setting (driver)	None
CC (forward voltage driver) (V)	22.0 - 44.0
Max load pr circuit - B10	8
Max load pr circuit - B16	14
Max load pr circuit - C10	18
Max load pr circuit - C16	29
Inrush current time (μ s)	300.0
Inrush current I _{max} (A)	20.0

DIMENSIONS	
Length (product) (mm)	127.0
Width (product) (mm)	43.0
Height (product) (mm)	28.0
Weight (product) (kg)	0.12

ENERGY AND CERTIFICATIONS	
CE mark	Yes