

**PRODUCT DATA SHEET**

Driver Phasecut 900mA Panel max 45W 25-50V 18i3 Male/EPN0034
 Art.no: 0300-26

*Lighting Solutions*

Driver Phasecut 900mA Panel max 45W 25-50V 18i3 Male/EPN0034



Phasecut driver for Panel Max 45W 900mA 22-40V Primary side 18i3 male connector Secondary side EPN0034 connector

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-20 - 50
Connection 1	18i3 male
Connection 2	EPN0034 female

**PRODUCT DATA SHEET**

Driver Phasecut 900mA Panel max 45W 25-50V 18i3 Male/EPN0034

Art.no: 0300-26

*Lighting Solutions*

DRIVER	
Manufacturer (driver)	AcTEC
Protection Class (driver)	2
Max Output Voltage (V)	60
Dimming Minimum Level (%)	1.0
Dimming Phasecut Type	Leading / Trailing edge
Dimming output type	Amplitude Modulation
IP (driver)	IP20
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	900 - null
CC (forward voltage driver) (V)	25.0 - 50.0
Max load pr circuit - B10	35
Max load pr circuit - B16	56
Max load pr circuit - C10	74
Max load pr circuit - C16	118
Inrush current time (μ s)	300.0
Inrush current I _{max} (A)	5.0

DIMENSIONS	
Length (product) (mm)	166.0
Width (product) (mm)	52.0
Height (product) (mm)	24.0
Weight (product) (kg)	0.2

MATERIALS AND SURFACES	
Color	White

ENERGY AND CERTIFICATIONS	
CE mark	Yes