

**PRODUCT DATA SHEET**

Driver Phasecut 350mA max 18W 26-52V 18i3&EPN0034

Art.no: 0300-27

*Lighting Solutions*

Driver Phasecut 350mA max 18W 26-52V 18i3&EPN0034



ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-20 - 50
Connection 1	18i3 male
Connection 2	EPN0034 female

DRIVER	
Manufacturer (driver)	AcTEC

**PRODUCT DATA SHEET**

Driver Phasecut 350mA max 18W 26-52V 18i3&EPN0034

Art.no: 0300-27

*Lighting Solutions*

DRIVER	
Protection Class (driver)	2
Max Output Voltage (V)	62
Dimming (driver)	Phase-Cut
Dimming Minimum Level (%)	1.0
Dimming Phasecut Type	Leading / Trailing edge
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	350 - null
Current setting (driver)	None
CC (forward voltage driver) (V)	26.0 - 52.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	15.0
Max load pr circuit - B10	35
Max load pr circuit - B16	56
Max load pr circuit - C10	74
Max load pr circuit - C16	118
Leakage current (mA)	5.0
Inrush current time (μ s)	300.0
Inrush current I _{max} (A)	5.0

DIMENSIONS	
Length (product) (mm)	120.0
Width (product) (mm)	45.0
Height (product) (mm)	28.0
Weight (product) (kg)	0.15

ENERGY AND CERTIFICATIONS	
CE mark	Yes